
MODEL NO- GEAPON-EX-1108

OLT series products is 1U high 19 inch rack mount product. The features of the OLT are small, convenient, flexible, easy to deploy, high performance. It is appropriate to deploy in a compact room environment.

The OLT can use for "Triple-Play", CPN, IP Camera, Enterprise LAN and IOT applications. It is a high performance product.

It provides 8GE and 8 SFP slots interface for uplink, and 8 EPON ports for downstream. It can support 512 ONU under 1:64 splitter ratio.

Functional Feature

✧ High Stability with low cost and flexible networking construction

- Eight fixed PON slots with 1:64 splitting ratio at most
- It could support 512 ONU maximally
- Maximum Transmission distance:20km (1:32 splitting ratio)

✧ Comprehensive Network Management

- In band and out band management;
- Support Telnet and local command lines management;
- EMS management based on standard SNMP protocol;
- Support online upgrading.

✧ Powerful QOS Functions

- Realize stable and efficient dynamic bandwidth allocation (DBA)
- Various OAM Functions
- ONU auto-detection and registration;
- Support LGMP and Snooping function;
- Support port flow control and flow shaping.

✧ Perfect to layer2 convergence exchange

- Support multiple uplink port and through the port bound function
- Support for the user provide optical and copper uplink port SFP slot access

Specifications

Item		Parameter
Uplink Port	QTY	16
	Copper	10/100/1000M auto-negotiable,RJ45:4pcs
	SFP	8 SFP slots
PON Port	QTY	8
	Physical Interface	SFP Slots
	Connector Type	1000BASE-PX20+
	Max splitting ratio	1:64
Management Ports		1*10/100/1000M auto-negotiable outband port 1CONSOLE port
PON Port Specification (Apply to C-Data PON module)	Transmission Distance	20KM
	PON port speed	Symmetrical 1.25Gbps
	Wavelength	1490nm TX,1310nm RX
	Connector	SC/PC
	Fiber Type	9/125μm SMF
	TX Power	+2.5~+7dBm
	Rx Sensitivity	-27dBm
	Saturation Optical Power	-6dBm
Management Mode		SNMP, Telnet, CLI management mode.
Management Function		Fan Group Detecting Port Status monitoring and configuration management; Layer-2 switch configuration such as Vlan, Trunk ,RSTP,IGMP ,QOS, etc; EPON management function: DBA ,ONU authorization, ACL ,QOS ,etc; Online ONU configuration and management User management Alarm management
Layer-two Switch		Support port Vlan and protocolVlan Support Vlan tag/Untag ,vlan transparent transmission; Support 4096 VLAN Support 802.3dd trunk Support RSTP Support QOS based on port ,VID,TOS and MAC address Support IGMP Snooping Support 802.3x flow control Support Port stability statistic and monitoring
EPON Function		Support port-based rate limitation and bandwidth control; In compliant with IEEE802.3ah Standard Up to 20KM transmission Distance Support data encryption, group broadcasting, port Vlan separation,

